


# Circular straight silencer

# SLU



## Dimensions and sound data



### Description

SLU 50 is a circular straight silencer with a connection diameter available between 80–315 mm.

Nominal insulation thickness 50 mm. Attenuation material is mineral wool. The SLU's are made of strong outer spiral seamed tube and an inner tube made of sheet steel with small openings to be able to withstand mechanical cleaning and at the same time not interfere with the insertion loss. The space between them is filled with mineral wool and a nonwoven cloth is inserted between inner tube and the attenuation material, to prevent fibers from the insulation getting into the duct system.

Tested according to ISO 7235 standard.

Special materials and sizes, please contact Lindab sales.

Ød <sub>1 nom</sub> mm	l <sub>nom</sub> mm	Attenuation in dB for centre frequency Hz								Ød <sub>y</sub> mm	l mm	m kg
		63	125	250	500	1k	2k	4k	8k			
80	300	1	5	8	15	25	25	21	15	190	300	2,0
80	600	2	8	14	28	49	50	47	24	190	600	3,0
80	900	3	10	21	40	50	50	50	34	190	900	5,0
80	1200	4	13	27	50	50	50	50	43	190	1200	7,0
100	300	1	5	7	15	25	25	21	13	210	360	2,0
100	600	1	7	12	25	43	48	35	20	210	660	3,0
100	900	2	10	17	34	50	50	49	28	210	960	5,0
100	1200	3	12	22	44	50	50	50	35	210	1260	7,0
125	300	0	4	5	13	23	20	16	11	235	365	3,0
125	600	1	5	10	22	39	37	26	16	235	665	4,0
125	900	1	7	14	30	50	50	37	21	235	965	7,0
125	1200	2	9	18	39	50	50	47	26	235	1265	9,0
160	300	0	3	5	11	22	16	11	7	270	370	3,0
160	600	1	4	8	19	37	28	17	11	270	670	6,0
160	900	1	5	12	27	50	39	24	14	270	970	8,0
160	1200	2	6	15	35	50	50	30	17	270	1270	10,0
200	300	0	2	4	9	19	11	7	5	310	385	4,0
200	600	1	3	8	15	28	19	12	8	310	685	7,0
200	900	2	4	11	21	37	28	16	10	310	985	10,0
200	1200	2	5	14	27	46	36	21	13	310	1285	12,0
250	600	1	2	6	14	26	14	8	7	365	600	9,0
250	900	1	3	9	19	38	19	11	9	365	900	12,0
250	1200	2	4	11	24	50	24	13	11	365	1200	15,0
315	300	0	1	2	6	12	5	4	4	427	300	12,0
315	600	0	2	4	10	22	9	6	7	427	600	12,0
315	1200	2	3	8	20	39	16	9	10	427	1200	24,0

There is given max. attenuation values of 50 dB in the table above.

### Order code

<b>Product</b>	SLU	aaa	bbbb	50
SLU				
<b>Connection dim. Ød<sub>1 nom</sub></b>	80 - 315 mm			
<b>Length in mm ( l<sub>nom</sub> )</b>	300 - 1200 mm			
<b>Insulation thickness</b>	50 mm			

Example: SLU -125- 600 - 50

