



Declaration of performance CE

Steel profiles for plasterboards

- I. Name and address of the producer
Lindab Profil AB, SE 269 82 Båstad, Sweden
- II. Plants producing the products
SE
- III. Name and address of the certification body
No external certification body required
- IV. Description of the products
 1. Type of product: Metal framing components for plasterboard systems
 2. Trade name: Lindab
 3. Types:

Studs: RE 45-160, RdB 45-160, RdBX 70-120, RdB7 45-160, RdBF 70-120, CW 75-150, CWX 50-150, KR45-200, FR 45-200, RP 70-95, RT 70-95, RU1 45-70, HR, HRT, RY 100-250 t 0,7-1,5, RYP 100-220 t 0,7-1,5, RYF 145-220 t 1,2-1,5

Runners: SK 25-95, SK43 45-120, SK55 45-160, SK100 45-160, SKP 45-95, SKP43 45-120, SKP55 45-160, SKT43 45-100, SKT55 45-160, KSK 45-200, FSK60 45-200, SKU 45-95 SKY 100-250 t 0,7-1,5, SKYP 100-220 t 0,7-1,5, SKYF 145-220 0,7-1,2

Other: HS, J, JL,LP, KLP, LPP, L50, L100, LPTI, LPTU, OPR, P, S 25-45, S7 25-45, PA, PD 25-45, PDP 25-45, PR, RCY 45-75, RZ 45-75, TSKA, BA 100-300, VBA, INPL, UBA
 4. Intended use
Support plasterboard systems
 5. Information accompanying the CE-mark

Reaction to fire

A1

Studs: RE 45-160, RdB 45-160, RdBX 70-120, RdB7 45-160, RdBF 70-120, CW 75-150, CWX 50-150, KR45-200, FR 45-200, RU1 45-70, HR, HRT, RY 100-250 t 0,7-1,5, RYP 100-220, RYF 145-220 t 1,2-1,5

Runners: SK 25-95, SK43 45-120, SK55 45-160, SK100 45-160, KSK 45-200, FSK60 45-200, SKU 45-95 SKY 100-250 t 0,7-1,5, SKYF 145-220 0,7-1,2

Other: HS, J, JL,LP, KLP, LPP, L50, L100, OPR, P, S 25-45, S7 25-45, PA, PD 25-45, PDP 25-45, PR, RCY 45-75, RZ 45-75, TSKA, BA 100-300, VBA, INPL, FRK, DK, UBA

NPD

Studs: RP 70-95, RT 70-95, HRT, RYP 100-220 t 0,7-1,5



Runners: SKP 45-95, SKP43 45-120, SKP55 45-160, SKT43 45-100, SKT55 45-160, SKYP 100-220 t 0,7-1,5,
Other: LPTI, LPTU

Yield strength

350 N/mm²

Studs: RdB7 45-160, KR100-200, FR 100-200, RY 100-250 t 0,7-1,5, RYP 100-220 t 0,7-1,5, RYF 145-220 t 1,2-1,5

Runners: KSK 100-200, FSK60 100-200, SKY 100-250 t 0,7-1,5, SKYP 100-220 t 0,7-1,5, SKYF 145-220 0,7-1,2

Other: KLP, P, S7 25-45, OPR, RZ 45-75, UBA

250 N/mm²

Studs: KR45-95, FR 45-95

Runners: KSK 45-95, FSK60 45-95

Other: INPL

NPD

Studs: RE 45-160, RdB 45-160, RdBX 70-120, RdB7 45-160, RdBF 70-120, RP 70-95, RT 70-95, RU1 45-70, CW 75-150, CWX 50-150, HR, HRT,

Runners: SK 25-95, SK43 45-120, SK55 45-160, SK100 45-160, SKP 45-95, SKP43 45-120, SKP55 45-160, SKT43 45-100, SKT55 45-160, SKU 45-95

Other: HS, J, JL, LP, LPP, L50, L100, LPTI, LPTU, OPR, S 25-45, PA, PD 25-45, PDP 25-45, PR, RCY 45-75, TSKA, BA 100-300, VBA, FRK, DK,

- V. Provision to which the products conform
The products conform to EN 14195
- VI. Provisions to use the product
None

Förslöv 2013-06-25

Johan Andersson
Product Manager
Lindab Profil AB