


Uninsulated aluminium flexible duct

COMDEC



Dimensions



Ød nom	Ød1 [mm]	O πd m	A $\pi d^2/4$ m ²	l [mm]	m [kg]
63	63	0,198	0,003	5000	0,55
80	82	0,258	0,005	10000	1,60
100	102	0,320	0,008	10000	1,90
125	127	0,399	0,013	10000	2,20
160	160	0,503	0,020	10000	3,00
200	203	0,638	0,032	10000	4,00
250	254	0,798	0,051	10000	5,40
315	318	0,999	0,079	10000	6,00
400	408	1,282	0,131	10000	10,0
500	510	1,602	0,204	10000	12,0

Description

Multiple layer product made up of a PVC coated aluminium into a flexible duct supported by a steel wire helix.

Applications

Suitable for use in general ventilation applications including fresh air intake and exhaust, and kitchen and bathroom.

Technical data

Duct materials	Aluminium PVC Steel wire helix
Temperature range	-30 to +140 °C
Packing	Individual box

Ordering example

Product	COMDEC	160	10000
Dimension Ød			
Length l			

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18