



Order code

Waterborne indoor climate solutions



Content



| Product | Page |
|--------------------|-------------|
| Plexus | 4 |
| Professor | 6 |
| Premum | 8 |
| Premax | 10 |
| Architect | 12 |
| Polaris | 14 |
| Plafond | 16 |
| Podium | 18 |
| Celo | 19 |
| Cabinett | 20 |
| Capella | 21 |
| Carat | 22 |
| Fasadium | 23 |
| Atrium C/H | 24 |
| Loggia | 25 |
| Atrium Plana | 26 |



Order code

Plexus

Product

| Plexus | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|----|----|----|
| <i>Ceiling adaption:</i> I, X, Y, Z, F | | | | | | | | | | | |
| <i>Air configuration:</i> S, L, M, H | | | | | | | | | | | |
| <i>Size:</i> 60, 62, 67, 120, 122 | | | | | | | | | | | |
| <i>Water connection:</i> 12 mm, Only ventilation | | | | | | | | | | | |
| <i>Air connection:</i> 125, 160 | | | | | | | | | | | |
| <i>Connection type:</i> A5, A6, B5, B6 (Plexus F: A1, A5, A6, B1, B5, B6) | | | | | | | | | | | |
| <i>Static nozzle pressure (Pa):</i> | | | | | | | | | | | |
| <i>Air volume (l/s):</i> | | | | | | | | | | | |
| <i>Color:</i> RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | | | | |
| <i>Perforation:</i> Slot, Dot x 2 Standard: Dot x 2 | | | | | | | | | | | |
| <i>Installation option:</i> No, Pendulums + z-brackets, Threaded rod M6 + z-brackets + screw nuts, Threaded rod M8 + z-brackets + screw nuts | | | | | | | | | | | |



Order code

Plexus

Optional features

| | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX |
|--|----|----|----|----|----|----|----|----|----|----|----|----|
| <i>Heating:</i> No, Yes | | | | | | | | | | | | |
| <i>Drypac:</i> No, Yes | | | | | | | | | | | | |
| <i>Drop down battery:</i> No, Yes (incl flexible hoses), Yes (excl flexible hoses) | | | | | | | | | | | | |
| <i>Aerator:</i> No, Aerator, 2 x Aerator | | | | | | | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR-12, 2 x Broen TTR-12 | | | | | | | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, 2 x A4004 24V NC on/off, 2 x AA5004 Modulating 0-10V NC | | | | | | | | | | | | |
| <i>Integrated regulation unit:</i> No, Regula Combi | | | | | | | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | | | | | | | |
| <i>Lindab eHybrid solution:</i> No, Master, Slave | | | | | | | | | | | | |
| <i>Integrated Presence sensor:</i> No, Regula Presence | | | | | | | | | | | | |
| <i>Integrated eHybrid damper:</i> No, Single damper 125 mm | | | | | | | | | | | | |



Order code

Professor

Product

| Professor | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| Type: I-45, I-60 F-45, F-60 | | | | | | | | | | | | | | | | |
| Water connection: 15 mm | | | | | | | | | | | | | | | | |
| Air connection: 100, 2x100 (opposite end) | | | | | | | | | | | | | | | | |
| Connection type: A1, A2, A3, A4, B1, B2, B3, B4 | | | | | | | | | | | | | | | | |
| Product length: 1.2 m - 3.6 m (In steps of 0.1 m) | | | | | | | | | | | | | | | | |
| Active length: Active length <= Product length - 0.3 m Standard = Product length - 0.3 m | | | | | | | | | | | | | | | | |
| Static nozzle pressure (Pa): | | | | | | | | | | | | | | | | |
| Air volume (l/s): | | | | | | | | | | | | | | | | |
| Air boost option (l/s): No, Requested max air volume | | | | | | | | | | | | | | | | |
| Distribution pattern: 30° (standard) 16° (medium) 0° (long) | | | | | | | | | | | | | | | | |
| Color: RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | | | | | | | | | |
| Perforation: Slot, Dot, Dot x 2 Standard: Slot | | | | | | | | | | | | | | | | |
| Air connection placement: High (default I), Low (default F) | | | | | | | | | | | | | | | | |
| Special ceiling adaption clip-in: No, Clip-in Metal, Clip-in Universal, Clip-in DG, Clip-in 58 T15, Clip-in 58 T24, Clip-in L | | | | | | | | | | | | | | | | |
| Installation option: No, Pendulums + z-brackets, Threaded rod M6 + z-brackets + screw nuts, Threaded rod M8 + z-brackets + screw nuts | | | | | | | | | | | | | | | | |



Order code

Professor

Optional features

| | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX |
|---|----|----|----|----|----|----|----|----|----|----|----|----|----|
| <i>Heating:</i> No, Yes | | | | | | | | | | | | | |
| <i>Drypac:</i> No, Yes | | | | | | | | | | | | | |
| <i>Aerator:</i> No, Aerator, 2 x Aerator | | | | | | | | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR-15, 2 x Broen TTR-15 | | | | | | | | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, 2 x A4004 24V NC on/off, 2 x AA5004 Modulating 0-10V NC | | | | | | | | | | | | | |
| <i>Integrated regulation unit:</i> No, Regula Combi | | | | | | | | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | | | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | | | | | | | | |
| <i>Integrated exhaust air valve:</i> No, KSU 100, KSU 125 | | | | | | | | | | | | | |
| <i>Lindab eHybrid solution:</i> No, Master, Slave | | | | | | | | | | | | | |
| <i>Integrated Presence sensor:</i> No, Regula Presence | | | | | | | | | | | | | |
| <i>Integrated eHybrid damper:</i> No, Single damper 100 mm, Double damper 100 mm | | | | | | | | | | | | | |
| <i>Integrated lighting:</i> No, Basic 2x28W 1.2m, Basic 2x35W 1.5m, DALI/T&D 2x28W 1.2m, DALI/T&D 2x35W 1.5m, Actilume 2x28W 1.2m, Actilume 2x35W 1.5m Basic: On/off DALI/T&D: DALI communication or Dimmable Actilume: Automatic lighting control, modulating | | | | | | | | | | | | | |



Order code

Premum

Product

| Premum | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|----|----|----|----|
| Type: I-60, I-62 X-60 | | | | | | | | | | | | |
| Water connection: 12 mm | | | | | | | | | | | | |
| Air connection: 125 | | | | | | | | | | | | |
| Connection type: A1, A2, A3, A4, A7, A8 B1, B2, B3, B4, B7, B8 C3, C4, C7, C8 D3, D4, D7, D8 | | | | | | | | | | | | |
| Product length: I-60, X-60: 1.2 m - 3.0 m (In steps of 0.1 m) I-62: 1.2 m, 1.8 m, 2.4 m, 3.0 m | | | | | | | | | | | | |
| Active length: Active length <= Product length - 0.3 m Standard = Product length - 0.3 m | | | | | | | | | | | | |
| Static nozzle pressure (Pa): | | | | | | | | | | | | |
| Air volume (l/s): | | | | | | | | | | | | |
| AirGuide: 30° (standard) 0° (long) | | | | | | | | | | | | |
| Color: RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | | | | | |
| Perforation: Slot, Dot x 2 Standard: Slot | | | | | | | | | | | | |
| Installation option: No, Pendulums + z-brackets, Threaded rod M6 + z-brackets + screw nuts, Threaded rod M8 + z-brackets + screw nuts | | | | | | | | | | | | |



Order code

Premium

Optional features

| | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX |
|--|----|----|----|----|----|----|----|----|----|----|----|----|
| <i>Heating:</i> No, Yes | | | | | | | | | | | | |
| <i>Drypac:</i> No, Yes | | | | | | | | | | | | |
| <i>Aerator:</i> No, Aerator, 2 x Aerator | | | | | | | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR-12, 2 x Broen TTR-12 | | | | | | | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, 2 x A4004 24V NC on/off, 2 x AA5004 Modulating 0-10V NC | | | | | | | | | | | | |
| <i>Integrated regulation unit:</i> No, Regula Combi | | | | | | | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | | | | | | | |
| <i>Integrated exhaust air valve:</i> No, KSU 125-type E, KSU 125-type F, KSU 125-type G, KSU 125-type H | | | | | | | | | | | | |
| <i>Lindab eHybrid solution:</i> No, Master, Slave | | | | | | | | | | | | |
| <i>Integrated Presence sensor:</i> No, Regula Presence | | | | | | | | | | | | |
| <i>Integrated eHybrid damper:</i> No, Single damper 125 mm, Double damper 125 mm | | | | | | | | | | | | |



Order code

Premax

Product

| Premax | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|----|----|----|----|
| Type: I-60, I-62 X-60 | | | | | | | | | | | | |
| Water connection: 12 mm, 15 mm (Heating: 12 mm only) | | | | | | | | | | | | |
| Air connection: 125 | | | | | | | | | | | | |
| Connection type: A1, A2, A3, A4, A7, A8 B1, B2, B3, B4, B7, B8 C3, C4, C7, C8 D3, D4, D7, D8 | | | | | | | | | | | | |
| Product length: 1.2 m - 1.8 m - 2.4 m - 3.0 m | | | | | | | | | | | | |
| Active length: Active length <= Product length - 0.3 m Standard = Product length - 0.3 m | | | | | | | | | | | | |
| Static nozzle pressure (Pa): | | | | | | | | | | | | |
| Air volume (l/s): | | | | | | | | | | | | |
| AirGuide: 30° (standard) 0° (long) | | | | | | | | | | | | |
| Color: RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | | | | | |
| Perforation: Slot, Dot x 2 Standard: Slot | | | | | | | | | | | | |
| Installation option: No, Pendulums + z-brackets, Threaded rod M6 + z-brackets + screw nuts, Threaded rod M8 + z-brackets + screw nuts | | | | | | | | | | | | |



Order code

Premax

Optional features

| | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX |
|--|----|----|----|----|----|----|----|----|----|----|----|----|
| <i>Heating:</i> No, Yes | | | | | | | | | | | | |
| <i>Drypac:</i> No, Yes | | | | | | | | | | | | |
| <i>Aerator:</i> No, Aerator, 2 x Aerator | | | | | | | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR-12, Broen TTR-15, 2 x Broen TTR-12, Broen TTR-12 + Broen TTR-15 | | | | | | | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, 2 x A4004 24V NC on/off, 2 x AA5004 Modulating 0-10V NC | | | | | | | | | | | | |
| <i>Integrated regulation unit:</i> No, Regula Combi | | | | | | | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | | | | | | | |
| <i>Integrated exhaust air valve:</i> No, KSU 125-type E, KSU 125-type F, KSU 125-type G, KSU 125-type H | | | | | | | | | | | | |
| <i>Lindab eHybrid solution:</i> No, Master, Slave | | | | | | | | | | | | |
| <i>Integrated Presence sensor:</i> No, Regula Presence | | | | | | | | | | | | |
| <i>Integrated eHybrid damper:</i> No, Single damper 125 mm, Double damper 125 mm | | | | | | | | | | | | |



Order code

Architect

Product

| Architect | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| Type: Moon, Wave, Oval, Square Box, Facet, Wing, body | | | | | | | | | | | | | | | |
| Water connection: 15 mm | | | | | | | | | | | | | | | |
| Air connection: 100, 2x100 (opposite end), 125, 2x125 (opposite end) | | | | | | | | | | | | | | | |
| Connection type: A1, A2, A3, A4 B1, B2, B3, B4 | | | | | | | | | | | | | | | |
| Product length: 1.2 m - 3.6 m (In steps of 0.1 m) | | | | | | | | | | | | | | | |
| Body length: 1.2 m - 3.6 m (In steps of 0.1 m) Standard = Product length = Body length | | | | | | | | | | | | | | | |
| Static nozzle pressure (Pa): | | | | | | | | | | | | | | | |
| Air volume (l/s): | | | | | | | | | | | | | | | |
| Air boost option (l/s): No, Requested max air volume | | | | | | | | | | | | | | | |
| Distribution pattern: 30° (standard) 16° (medium) 0° (long) | | | | | | | | | | | | | | | |
| Color: RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | | | | | | | | |
| Perforation: Slot (50%), Slot (33%), Line, Dot, Dot x 2 Standard: Slot (50%) | | | | | | | | | | | | | | | |
| Installation option: No, Pendulums + z-brackets, Threaded rod M6 + z-brackets + screw nuts, Threaded rod M8 + z-brackets + screw nuts | | | | | | | | | | | | | | | |
| Installation option (if Product length > Body length): No, Wall mounting bracket, Ceiling mounting bracket | | | | | | | | | | | | | | | |



Order code

Architect

Optional features

| | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX |
|---|----|----|----|----|----|----|----|----|----|----|----|----|
| <i>Heating:</i> No, Yes | | | | | | | | | | | | |
| <i>Drypac:</i> No, Yes | | | | | | | | | | | | |
| <i>Aerator:</i> No, Aerator, 2 x Aerator | | | | | | | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR-15, 2 x Broen TTR-15 | | | | | | | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, 2 x A4004 24V NC on/off, 2 x AA5004 Modulating 0-10V NC | | | | | | | | | | | | |
| <i>Integrated regulation unit:</i> No, Regula Combi | | | | | | | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | | | | | | | |
| <i>Lindab eHybrid solution:</i> No, Master, Slave | | | | | | | | | | | | |
| <i>Integrated Presence sensor:</i> No, Regula Presence | | | | | | | | | | | | |
| <i>Integrated eHybrid damper:</i> No, Single damper 100 mm, Single damper 125 mm | | | | | | | | | | | | |
| <i>Integrated lighting:</i> No, Basic 2x28W 1.2m, Basic 2x35W 1.5m, DALI/T&D 2x28W 1.2m, DALI/T&D 2x35W 1.5m, Actilume 2x28W 1.2m, Actilume 2x35W 1.5m Basic: On/off DALI/T&D: DALI communication or Dimmable Actilume: Automatic lighting control, modulating | | | | | | | | | | | | |



Order code

Polaris

Product

| Polaris | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|--|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| Type: I-60, S-30, S-60 | | | | | | | | | | | | | | | |
| Water connection: 15, 22 mm | | | | | | | | | | | | | | | |
| Air connection: I-60: 125, 2x125 (opposite end), 4x100 S-30/60: 100, 2x100 (same end) | | | | | | | | | | | | | | | |
| Connection type: I-60: A1, A2, A3, A4, A7, A8, B1, B2, B3, B4, B7, B8, C1, C2, C3, C4, C7, C8, D1, D2, D3, D4, D7, D8 S-30/S-60: A1L, A1R, A3L, A3R | | | | | | | | | | | | | | | |
| Product length: 1.2 m - 3.6 m (In steps of 0.1 m) | | | | | | | | | | | | | | | |
| Active length: Active length <= Product length - 0.3 m Standard = Product length - 0.3 m | | | | | | | | | | | | | | | |
| Static nozzle pressure (Pa): | | | | | | | | | | | | | | | |
| Air volume (l/s): | | | | | | | | | | | | | | | |
| Air boost option (l/s): No, Requested max air volume | | | | | | | | | | | | | | | |
| Distribution pattern: 30° (standard) 16° (medium) 0° (long) | | | | | | | | | | | | | | | |
| Color: RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | | | | | | | | |
| Perforation: Slot, Dot x 2 Standard: Slot | | | | | | | | | | | | | | | |
| Special ceiling adaption clip-in: No, Clip-in Metal, Clip-in Universal, Clip-in DG, Clip-in 58 T15, Clip-in 58 T24, Clip-in L | | | | | | | | | | | | | | | |
| Installation option: No, Pendulums + z-brackets, Threaded rod M6 + z-brackets + screw nuts, Threaded rod M8 + z-brackets + screw nuts | | | | | | | | | | | | | | | |



Order code

Polaris

Optional features

| | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX |
|--|----|----|----|----|----|----|----|----|----|----|----|
| <i>Heating:</i> No, Yes | | | | | | | | | | | |
| <i>Drypac:</i> No, Yes | | | | | | | | | | | |
| <i>Aerator:</i> No, Aerator, 2 x Aerator | | | | | | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR-15, 2 x Broen TTR-15, 3 x Broen TTR-15 (Cooling 22 mm requires 2 x Broen TTR-15) | | | | | | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, 2 x A4004 24V NC on/off, 2 x AA5004 Modulating 0-10V NC | | | | | | | | | | | |
| <i>Integrated regulation unit:</i> No, Regula Combi | | | | | | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | | | | | | |
| <i>Lindab eHybrid solution:</i> No, Master, Slave | | | | | | | | | | | |
| <i>Integrated Presence sensor:</i> No, Regula Presence | | | | | | | | | | | |
| <i>Integrated eHybrid damper:</i> No, Single damper 125 mm | | | | | | | | | | | |



Order code

Plafond

Product

| Plafond | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|----|----|----|----|
| <i>Type:</i> B, C, D | | | | | | | | | | | | |
| <i>Water connection:</i> 15 mm | | | | | | | | | | | | |
| <i>Air connection:</i> 100, 2x100 (opposite end) | | | | | | | | | | | | |
| <i>Connection type:</i> A1L, A1R, A2L, A2R, A3L, A3R, A4L, A4R, B1L, B1R, B2L, B2R, B3L, B3R, B4L, B4R | | | | | | | | | | | | |
| <i>Product length:</i> 1.2 m - 3.6 m (In steps of 0.1 m) | | | | | | | | | | | | |
| <i>Active length:</i> Active length <= Product length - 0.5 m Standard = Product length - 0.5 m | | | | | | | | | | | | |
| <i>Static nozzle pressure (Pa):</i> | | | | | | | | | | | | |
| <i>Air volume (l/s):</i> | | | | | | | | | | | | |
| <i>Air boost option (l/s):</i> No, Requested max air volume | | | | | | | | | | | | |
| <i>Distribution pattern:</i> 30° (standard) 16° (medium) 0° (long) | | | | | | | | | | | | |
| <i>Color:</i> RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | | | | | |
| <i>Perforation:</i> Slot, Dot, Dot x 2 Standard: Slot (C), No perforation (B, D) | | | | | | | | | | | | |



Order code

Plafond

Optional features

| | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX |
|--|----|----|----|----|----|----|----|----|----|----|----|----|
| <i>Heating:</i> No, Yes | | | | | | | | | | | | |
| <i>Drypac:</i> No, Yes | | | | | | | | | | | | |
| <i>Aerator:</i> No, Aerator, 2 x Aerator | | | | | | | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR-15, 2 x Broen TTR-15 | | | | | | | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, 2 x A4004 24V NC on/off, 2 x AA5004 Modulating 0-10V NC | | | | | | | | | | | | |
| <i>Integrated regulation unit:</i> No, Regula Combi | | | | | | | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | | | | | | | |
| <i>Integrated exhaust air valve:</i> No, KSU 100, KSU 125 | | | | | | | | | | | | |
| <i>Lindab eHybrid solution:</i> No, Master, Slave | | | | | | | | | | | | |
| <i>Integrated Presence sensor:</i> No, Regula Presence | | | | | | | | | | | | |
| <i>Integrated eHybrid damper:</i> No, Single damper 100 mm | | | | | | | | | | | | |



Order code

Podium

Product

| Podium | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|----|
| <i>Width:</i> 17, 35, 53 | | | | | | | | | |
| <i>Water connection:</i> 10, 12, 15, 22 mm | | | | | | | | | |
| <i>Air connection:</i> 100 | | | | | | | | | |
| <i>Connection type:</i> A1, A2, A3, A4, A13, A14, A23, A24 B1, B2, B3, B4, B13, B14, B23, B24 | | | | | | | | | |
| <i>Product length:</i> 1.2 m - 6.0 m (In steps of 0.1 m) | | | | | | | | | |
| <i>Color:</i> RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | | |
| <i>External water connection:</i> 10 to 15 mm, 12 to 15 mm | | | | | | | | | |
| <i>Installation option:</i> No, Pendulums | | | | | | | | | |
| <i>Hygiene hood:</i> No, Yes (only width 40, 60) | | | | | | | | | |

Optional features

| | xx | xx | xx | xx | xx | xx |
|--|----|----|----|----|----|----|
| <i>Heating:</i> No, Yes | | | | | | |
| <i>Aerator:</i> No, Aerator | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR, 2 x Broen TTR | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, 2 x A4004 24V NC on/off, 2 x AA5004 Modulating 0-10V NC | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | |



Order code

Celo

Product

| Celo | XX | XX | XX | XX | XX | XX | XX | XX | XX | XX |
|---|----|----|----|----|----|----|----|----|----|----|
| <i>Water connection:</i> 15 mm | | | | | | | | | | |
| <i>Air connection:</i> 80, 2x80 (opposite end) | | | | | | | | | | |
| <i>Connection type:</i> A1L, A1R, A3L, A3R | | | | | | | | | | |
| <i>Product length:</i> 1.2 m - 3.6 m (In steps of 0.1 m) | | | | | | | | | | |
| <i>Static nozzle pressure (Pa):</i> | | | | | | | | | | |
| <i>Air volume (l/s):</i> | | | | | | | | | | |
| <i>Air boost option (l/s):</i> No, Requested max air volume | | | | | | | | | | |
| <i>Distribution pattern:</i> 30° (standard) 16° (medium) 0° (long) | | | | | | | | | | |
| <i>Color:</i> RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | | | |
| <i>Installation option:</i> No, Pendulums + z-brackets, Threaded rod M6 + z-brackets + screw nuts, Threaded rod M8 + z-brackets + screw nuts | | | | | | | | | | |

Optional features

| | XX | XX | XX | XX | XX | XX |
|--|----|----|----|----|----|----|
| <i>Drypac:</i> No, Yes | | | | | | |
| <i>Aerator:</i> No, Aerator | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR-15 | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | |



Order code

Cabinett

Product

| Cabinett | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|
| <i>Type:</i> A-42, F-42, K-60 | | | | | | | |
| <i>Water connection:</i> 15 mm | | | | | | | |
| <i>Connection type:</i> 1, 2 | | | | | | | |
| <i>Product length:</i> 1.2 m - 3.6 m (In steps of 0.1 m) | | | | | | | |
| <i>Color:</i> RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | |
| <i>Installation option:</i> No, Pendulums + z-brackets, Threaded rod M6 + z-brackets + screw nuts, Threaded rod M8 + z-brackets + screw nuts | | | | | | | |
| <i>Perforation:</i> Slot, Dot x 2 Not available on F-42 | | | | | | | |

Optional features

| | xx | xx | xx | xx | xx | xx | xx |
|--|----|----|----|----|----|----|----|
| <i>Drypac:</i> No, Yes | | | | | | | |
| <i>Aerator:</i> No, Aerator | | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR-15 | | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, | | | | | | | |
| <i>Integrated regulation unit:</i> No, Regula Combi | | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | | |



Order code

Capella

Product

| Capella | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|
| <i>Width:</i> 17, 35, 53 | | | | | | | | |
| <i>Water connection:</i> 10, 12, 15, 22 mm | | | | | | | | |
| <i>Connection type:</i> 1, 2, 3, 4, 13, 14, 23, 24 | | | | | | | | |
| <i>Product length:</i> 1.2 m - 6.0 m (In steps of 0.1 m) | | | | | | | | |
| <i>Color:</i> RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | |
| <i>External water connection:</i> 10 to 15 mm, 12 to 15 mm | | | | | | | | |
| <i>Installation option:</i> No, Pendulums | | | | | | | | |
| <i>Hygiene hood:</i> No, Yes (only width 40, 60) | | | | | | | | |

Optional features

| | xx | xx | xx | xx | xx | xx |
|--|----|----|----|----|----|----|
| <i>Heating:</i> No, Yes | | | | | | |
| <i>Aerator:</i> No, Aerator | | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR, 2 x Broen TTR | | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, 2 x A4004 24V NC on/off, 2 x AA5004 Modulating 0-10V NC | | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | | |



Order code

Carat

Product

| Carat | XX | XX | XX | XX | XX | XX | XX | XX |
|---|----|----|----|----|----|----|----|----|
| <i>Width:</i> 31, 44, 58, 71, 84 | | | | | | | | |
| <i>Water connection:</i> 10, 12, 15, 22, 28 mm | | | | | | | | |
| <i>Connection type:</i> 1, 3, 13 | | | | | | | | |
| <i>Product length:</i> 1.2 m - 6.0 m (In steps of 0.1 m) | | | | | | | | |
| <i>Color:</i> RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | |
| <i>External water connection:</i> 10 to 15 mm, 12 to 15 mm | | | | | | | | |
| <i>Installation option:</i> No, Pendulums + z-brackets, Threaded rod M6 + z-brackets + screw nuts, Threaded rod M8 + z-brackets + screw nuts | | | | | | | | |
| <i>Edge list:</i> No, Yes | | | | | | | | |

Optional features

| | XX | XX | XX | XX | XX |
|--|----|----|----|----|----|
| <i>Aerator:</i> No, Aerator | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | |



Order code

Fasadium

Product

| Fasadium | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|----|
| Type: | | | | | | | | | |
| 24 | | | | | | | | | |
| Product length: | | | | | | | | | |
| 600, 700, 800, 1000, 1200, 1500 | | | | | | | | | |
| Height: | | | | | | | | | |
| Standard, Low | | | | | | | | | |
| Air connection: | | | | | | | | | |
| 100, 160, 200 | | | | | | | | | |
| Floor connection: | | | | | | | | | |
| 80, 100 (only on air connection 100 mm) | | | | | | | | | |
| Water connection side: | | | | | | | | | |
| Right, Left | | | | | | | | | |
| Static nozzle pressure (Pa): | | | | | | | | | |
| Air volume (l/s): | | | | | | | | | |

Optional features

| | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|----|
| Heating: | | | | | | | | | |
| No, Yes | | | | | | | | | |
| Drypac: | | | | | | | | | |
| No, Yes | | | | | | | | | |
| Aerator: | | | | | | | | | |
| No, Aerator, 2 x Aerator | | | | | | | | | |
| Integrated water valves: | | | | | | | | | |
| No, Broen TTV, 2 x Broen TTV | | | | | | | | | |
| Integrated actuator to water valves: | | | | | | | | | |
| No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, 2 x A4004 24V NC on/off, 2 x AA5004 Modulating 0-10V NC | | | | | | | | | |
| Mounted flexible hoses: | | | | | | | | | |
| No, Yes | | | | | | | | | |
| Integrated regulation unit: | | | | | | | | | |
| No, Regula Combi | | | | | | | | | |
| Integrated Connection card: | | | | | | | | | |
| No, Regula Connect Basic, Regula Connect Multi | | | | | | | | | |
| Integrated Condensation protection: | | | | | | | | | |
| No, Regula Secura | | | | | | | | | |



Order code

Atrium C/H

Product

| Atrium C/H | xx | xx | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|----|----|
| <i>Width:</i> 33, 60, 87 | | | | | | | | | | |
| <i>Water connection:</i> 10, 12, 15, 22 mm | | | | | | | | | | |
| <i>Connection type:</i> 1, 2, 13, 14, 23, 24 | | | | | | | | | | |
| <i>Product length:</i> 1.2 m - 6.0 m (In steps of 0.1 m) | | | | | | | | | | |
| <i>Color:</i> RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | | | |
| <i>Perforation:</i> No, Yes | | | | | | | | | | |
| <i>Hygiene sealing front:</i> No, Yes | | | | | | | | | | |
| <i>Hygiene sealing backside:</i> No, Yes | | | | | | | | | | |
| <i>External water connection:</i> 10 to 15 mm, 12 to 15 mm | | | | | | | | | | |
| <i>Installation option:</i> No, Pendulums, Direct on ceiling mounting brackets | | | | | | | | | | |

Optional features

| | xx | xx | xx | xx | xx |
|--|----|----|----|----|----|
| <i>Aerator:</i> No, Aerator | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | |



Order code

Loggia

Product

| Loggia | xx | xx | xx | xx | xx | xx | xx | xx |
|---|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| <i>Width:</i> 33, 60, 87 | | | | | | | | |
| <i>Water connection:</i> 10, 12, 15, 22 mm | | | | | | | | |
| <i>Connection type:</i> 1, 2, 13, 14, 23, 24 | | | | | | | | |
| <i>Product length:</i> 1.2 m - 6.0 m (In steps of 0.1 m) | | | | | | | | |
| <i>Color:</i> RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | |
| <i>Perforation:</i> No, Yes | | | | | | | | |
| <i>External water connection:</i> 10 to 15 mm, 12 to 15 mm | | | | | | | | |
| <i>Installation option:</i> No, Pendulums, Direct on ceiling mounting brackets | | | | | | | | |

Optional features

| | xx | xx | xx | xx | xx |
|--|-----------|-----------|-----------|-----------|-----------|
| <i>Aerator:</i> No, Aerator | | | | | |
| <i>Integrated water valves:</i> No, Broen TTR | | | | | |
| <i>Integrated actuator to water valves:</i> No, A4004 24V NC on/off, AA5004 Modulating 0-10V NC, | | | | | |
| <i>Integrated Connection card:</i> No, Regula Connect Basic, Regula Connect Multi | | | | | |
| <i>Integrated Condensation protection:</i> No, Regula Secura | | | | | |



Order code

Atrium Plana

Product

| Atrium Plana | xx | xx | xx | xx | xx | xx | xx | xx |
|---|----|----|----|----|----|----|----|----|
| <i>Type:</i> C, H, H+C | | | | | | | | |
| <i>Width:</i> 40, 60 cm 90 cm (only H+C) | | | | | | | | |
| <i>Water connection:</i> 10 mm | | | | | | | | |
| <i>Connection type:</i> 1, 2 | | | | | | | | |
| <i>Product length:</i> 0.6 – 1.2 – 1.8 – 2.4 – 3.0 m | | | | | | | | |
| <i>Color:</i> RAL 9010, RAL 9003, RAL 9005, RAL 9006, NCS S0500N Standard: RAL 9003 or RAL 9010 (gloss value 30) Other colors available upon request | | | | | | | | |
| <i>External water connection:</i> 10 to 15 mm | | | | | | | | |
| <i>Installation option:</i> No, Pendulums, Direct on ceiling mounting brackets | | | | | | | | |

Support
Hjælp
Hjälp
Tuotetuki
Unterstützung
Supporto

UK - Here you can find product updates/mounting instructions and support telephone number/mail.

www.lindab.com

Right to alterations reserved.

DK - Her kan du finde seneste produkt opdateringer/ montagevejledninger samt support tlf. nr/mail.

www.lindab.dk

Ret til ændringer forbeholdes.

SE - Här kan du alltid hitta senaste produktuppdateringarna/montageanvisningarna samt support tel. /e-mail.

www.lindab.se

Rätt till ändringar förbehålles.

FI - Täältä löydät uusimmat tuotetiedot ja asennusohjeet sekä tuotetuen yhteystiedot.

www.lindab.fi

Oikeus muutoksiin pidätetään.

DE - Hier finden Sie aktuelle Produktinformationen/ Montageanleitungen und Telefonnummer/ E-Mail-Adressen der Ansprechpartner.

www.lindab.de

Änderungen vorbehalten.

IT - Qui potete trovare istruzioni di montaggio, informazioni sul prodotto ed un supporto tecnico qualificato
Tel. 011 9952099 - e-mail: lindab@lindab.it

www.lindab.it

Soggetto a modifica senza obbligo di preavviso.

FR - Vous trouverez les fiches produits ou de montage actualisées ainsi que les coordonnées du support téléphonique à l'adresse suivante :

www.lindab.fr

Toutes modifications réservées.

**Do you have trouble finding your local contacts
please go to:**

www.lindab.com

Order code - 05082014



www.lindab.com