



Perforated exhaust plate

PKY/PCY



Description

PKY/PCY is a “diffuser” without duct connection for installation in T-rail ceilings. PKY/PCY is used in situations where air is to be exhausted over a suspended ceiling, and a sufficient opening is required in the ceiling for the air to pass through.

- Architecturally and financially attractive “diffuser” solution for exhaust of air over a suspended ceiling
- Can be adapted for many different types of ceiling
- Low pressure loss and large air capacity

Maintenance

The visible parts of the diffuser can be wiped with a damp cloth.

Materials and finish

Material: Galvanised steel
 Standard finish: Powder-coated
 Standard colour: RAL 9010, gloss 30

The diffuser is available in other colours. Please contact Lindab’s sales department for further information.

Ordering example

Product **PKY/PCY** **aaa**
 Type _____
 Size _____
 Ceiling system - see introductory summary.

Dimensions

PKY

A Size	B mm	C mm	Free area m ²	Curve no.	m kg
500	495	467	0,085	1	1,3
600	595	567	0,125	2	1,8
625	620	597	0,138	3	1,9

PCY

A Size	B mm	C mm	Free area m ²	Curve no.	m kg
500	495	400	0,043	4	1,6
600	595	490	0,064	5	2,1
625	620	490	0,064	5	2,2

Pressure loss [Pa]

