

SAFETY DATA SHEET

Lindab Mastic Acryl

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Lindab Mastic Acryl

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Sealing and filling

▼ Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

▼ Company and address

Lindab AB

Stålhögavägen 115

SE 269 82 Båstad

Sweden

Contact person

ventilation@lindab.com

Revision

01/11/2022

SDS Version

3.0

Date of previous version

14/08/2020 (2.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.2. Label elements

▼ Hazard pictogram(s)

▼ Signal word

Not applicable.

▼ Hazard statement(s)

Not applicable.

Safety statement(s)

General

-

Prevention

-

Response

-

Storage

-

Disposal

-

▼ Hazardous substances

None known.

▼ Additional labelling

EUH208, Contains 1,2-benzisothiazol-3(2H)-one, Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

EUH210, Safety data sheet available on request.

Active substance(s):

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (0.00149 g/100g)

2.3. Other hazards

▼ Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Titanium dioxide	CAS No.: 13463-67-7 EC No.: 236-675-5 UK-REACH: Index No.:	3-5%		
1,2-benzisothiazol-3(2H)-one	CAS No.: 2634-33-5 EC No.: 220-120-9 UK-REACH: Index No.: 613-088-00-6	<0.05%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 (SCL: 0.05 %) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)	
Butyl acrylate	CAS No.: 141-32-2 EC No.: 205-480-7 UK-REACH: Index No.: 607-062-00-3	<0.01%	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 STOT SE 3, H335	[1]
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: 911-418-6 UK-REACH: Index No.:	<0.0015%	EUH071 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Irrit. 2, H315 (SCL: 0.06 %) Skin Sens. 1A, H317 (SCL: 0.0015 %) Eye Dam. 1, H318 Acute Tox. 2, H330 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	
vinyl acetate	CAS No.: 108-05-4 EC No.: 203-545-4 UK-REACH: Index No.: 607-023-00-0	<0.0015%	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT SE 3, H335 Carc. 2, H351	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

▼ Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

▼ Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

▼ Burns

Not applicable.

4.2. ▼ Most important symptoms and effects, both acute and delayed

This product contains substances that may trigger an allergic reaction in already sensitized persons.

4.3. ▼ Indication of any immediate medical attention and special treatment needed

None known.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. ▼ Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

6.1. ▼ Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. ▼ Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. ▼ Methods and material for containment and cleaning up

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. ▼ Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼ Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. ▼ Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

▼ Recommended storage material

Always store in containers of the same material as the original container.

▼ Storage temperature

> 0°C

▼ Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. ▼ Control parameters

Titanium dioxide

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

propane-1,2-diol

Long term exposure limit (8 hours) (ppm): 150(total)

Long term exposure limit (8 hours) (mg/m³): 474(total)/10(particulates)

Butyl acrylate

Long term exposure limit (8 hours) (ppm): 1

Long term exposure limit (8 hours) (mg/m³): 5

Short term exposure limit (15 minutes) (ppm): 5

Short term exposure limit (15 minutes) (mg/m³): 26

vinyl acetate

Long term exposure limit (8 hours) (ppm): 5

Long term exposure limit (8 hours) (mg/m³): 17,6

Short term exposure limit (15 minutes) (ppm): 10

Short term exposure limit (15 minutes) (mg/m³): 35,2

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.

EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

propane-1,2-diol

Duration	Route of exposure	DNEL
Long term – Local effects - General population	Inhalation	10 mg/m ³
Long term – Local effects - Workers	Inhalation	10 mg/m ³
Long term – Systemic effects - General population	Inhalation	50 mg/m ³
Long term – Systemic effects - Workers	Inhalation	168 mg/m ³

Titanium dioxide

Duration	Route of exposure	DNEL
Long term – Local effects - Workers	Inhalation	10 mg/m ³
Long term – Systemic effects - General population	Oral	700 mg/kg

vinyl acetate

Duration	Route of exposure	DNEL
Long term – Systemic effects - Workers	Dermal	420 µg/kgbw/day
Long term – Local effects - Workers	Inhalation	17.6 mg/m ³
Long term – Systemic effects - Workers	Inhalation	17.6 mg/m ³
Short term – Local effects - Workers	Inhalation	35.2 mg/m ³
Short term – Systemic effects - Workers	Inhalation	35.2 mg/m ³

▼ PNEC

propane-1,2-diol

Route of exposure	Duration of Exposure	PNEC
Freshwater		260 mg/L
Freshwater sediment		572 mg/kg
Intermittent release (freshwater)		183 mg/L
Marine water		26 mg/L
Marine water sediment		57.2 mg/kg
Sewage treatment plant		20 g/L
Soil		50 mg/kg

Titanium dioxide

Route of exposure	Duration of Exposure	PNEC
Air		

Freshwater
Freshwater sediment
Marine water
Marine water sediment
Predators
Sewage treatment plant
Soil

vinyl acetate

Route of exposure	Duration of Exposure	PNEC
Freshwater		16 µg/L
Freshwater sediment		67 µg/kg
Intermittent release (freshwater)		126 µg/L
Marine water		1.6 µg/L
Marine water sediment		6.7 µg/kg
Sewage treatment plant		6 mg/L
Soil		3.5 µg/kg

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

▼ General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼ Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

▼ Measures to avoid environmental exposure

No specific requirements.

8.3. Individual protection measures, such as personal protective equipment

▼ Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

No specific requirements

Skin protection

Recommended	Type/Category	Standards
No specific requirements.	-	-

▼ Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
	Nitrile	0.1	>60	EN374-2, EN388



When applying the sealant with a caulking gun and when finishing with a joint nail, work can be carried out without gloves if skin contact is avoided.

Eye protection

Type	Standards
No specific requirements	-

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Paste

▼ Colour

According to specification

▼ Odour / Odour threshold

Characteristic

pH

7-9

Density (g/cm³)

1.62

▼ Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

▼ Particle characteristics

Testing not relevant or not possible due to the nature of the product.

Phase changes

▼ Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

▼ Boiling point (°C)

100

▼ Vapour pressure

Testing not relevant or not possible due to the nature of the product.

▼ Relative vapour density

Testing not relevant or not possible due to the nature of the product.

▼ Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

▼ Flash point (°C)

Testing not relevant or not possible due to the nature of the product.

▼ Ignition (°C)

420

▼ Auto flammability (°C)

Testing not relevant or not possible due to the nature of the product.

▼ Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

▼ Solubility in water

Completely soluble

▼ n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

▼ Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

▼ VOC (g/L)

0

▼ Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. ▼ Reactivity

No data available.

10.2. ▼ Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. ▼ Possibility of hazardous reactions

None known.

10.4. ▼ Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

Product/substance	Titanium dioxide
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	>10000 ·
Other information	

Product/substance	propane-1,2-diol
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	20 g/kg ·
Other information	

Product/substance	propane-1,2-diol
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	208 g/kg ·
Other information	

Product/substance	1,2-benzisothiazol-3(2H)-one
Test method	
Species	Rat
Route of exposure	Dermal
Test	LD50
Result	>2000 mg/L
Other information	

Product/substance	1,2-benzisothiazol-3(2H)-one
Test method	
Species	Rat
Route of exposure	Oral
Test	LD lo
Result	597 mg/L
Other information	

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	49,6-75 mg/kg ·
Other information	

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	0,33 mg/l, 4 h aerosol ·

Other information

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	141 mg/kg ·
Other information	

▼ Skin corrosion/irritation

Product/substance	1,2-benzisothiazol-3(2H)-one
Test method	
Species	Rabbit
Duration	No data available.
Result	Adverse effect observed (Moderately irritating)
Other information	

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

▼ Respiratory sensitisation

Based on available data, the classification criteria are not met.

▼ Skin sensitisation

Product/substance	1,2-benzisothiazol-3(2H)-one
Test method	
Species	
Result	Adverse effect observed (sensitising)
Other information	

Product/substance	Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	OECD 406
Species	Guinea pig
Result	Adverse effect observed (sensitising)
Other information	

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

▼ Long term effects

None known.

▼ Endocrine disrupting properties

None known.

▼ Other information

Titanium dioxide has been classified by IARC as a group 2B carcinogen.

Butyl acrylate has been classified by IARC as a group 3 carcinogen.

vinyl acetate has been classified by IARC as a group 2B carcinogen.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance	propane-1,2-diol
Test method	
Species	Daphnia
Compartment	
Duration	48 hours
Test	EC50
Result	>10000 mg/l ·

Other information

Product/substance propane-1,2-diol
 Test method
 Species Fish
 Compartment
 Duration 48 hours
 Test LC50
 Result >10000 mg/l ·
 Other information

Product/substance 1,2-benzisothiazol-3(2H)-one
 Test method
 Species Fish
 Compartment
 Duration 96 hours
 Test LC50
 Result 0,74 mg/L
 Other information

Product/substance 1,2-benzisothiazol-3(2H)-one
 Test method
 Species Daphnia
 Compartment
 Duration 48 hours
 Test EC50
 Result 2,44 mg/L
 Other information

Product/substance Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
 Test method
 Species Algae
 Compartment
 Duration 72 hours
 Test EC50
 Result 0,027 mg/l ·
 Other information

12.2. ▼ Persistence and degradability

Product/substance Titanium dioxide
 Biodegradable No
 Test method
 Result

Product/substance propane-1,2-diol
 Biodegradable Yes
 Test method
 Result

Product/substance Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
 Biodegradable Yes
 Test method OECD 301 D
 Result >60%

12.3. ▼ Bioaccumulative potential

Product/substance propane-1,2-diol
 Test method
 Potential bioaccumulation No
 LogPow -0,9200
 BCF 3
 Other information

Product/substance Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
 Test method
 Potential bioaccumulation No
 LogPow No data available.
 BCF 3.6
 Other information

12.4. ▼ Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. ▼ Endocrine disrupting properties

None known.

12.7. ▼ Other adverse effects

None known.

SECTION 13: Disposal considerations

▼ Waste treatment methods

Product is not covered by regulations on dangerous waste.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09

▼ Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

▼ Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. ▼ Special precautions for user

Not applicable.

14.7. ▼ Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

▼ Restrictions for application

Must not be used by persons suffering from acrylic dermatitis.

▼ Demands for specific education

No specific requirements.

▼ SEVESO - Categories / dangerous substances

Not applicable.

Biocidal Products Regulations

Product type: PT1 - Human hygiene

▼ Restrictions on use:

-

▼ Directions for use and dose rate:

-

▼ Additional information:

-

▼ Additional information

Not applicable.

▼ Sources

In accordance with Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products as retained and amended in UK law.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H314, Corrosive to the respiratory tract.
H225, Highly flammable liquid and vapour.
H226, Flammable liquid and vapour.
H301, Toxic if swallowed.
H302, Harmful if swallowed.
H310, Fatal in contact with skin.
H314, Causes severe skin burns and eye damage.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H330, Fatal if inhaled.
H332, Harmful if inhaled.
H335, May cause respiratory irritation.
H351, Suspected of causing cancer.
H400, Very toxic to aquatic life.
H410, Very toxic to aquatic life with long lasting effects.

▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

▼ Additional information

Not applicable.

▼ The safety data sheet is validated by

Product Safety Department

▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en