

Shears

TRC200



Description

Cordless shears to cut circular ducts of sheet metal thickness up to 4 x 0,9 mm.

The shears can be fitted on the workbench (SR cutter), SRCS2. Note that to be able to connect TRC200 to SRCS2, the adapter CSAD must be used, see [mounting instructions](#).

The shears can also be used for other types of metal cutting.

Delivery includes:

- TruTool C200 LiHD 18V (1 pcs.)
- Set spiro - KNSSR (mounted on the machine)
- 18V LiHD 4Ah rechargeable battery (2 pcs.)
- 12V - 36V recharger LG (1 pcs.)
- TRUMPF Box S2 (1 pcs.)

Technical data

Dimensions:

Length: 394 mm
 Height: 119 mm
 Weight (incl. battery): 2,4 kg
 Battery type: LiHD Voltage: 18V
 Working speed (max): 10 m/min

Maximum sheet thickness
 Steel with breaking strength:
 400 N/mm² : 4 x 0,9 mm
 600 N/mm² : 4 x 0,6 mm

KNSRA 179 009

Set curve

1 x curve cutter, 2 x cutting blades



KNSSR 179 008

Set Spiro

1 x SC cutter, 2 x toothed cutting blade



CSAD 179 007

Adapter when using TRC200 on SR cutter.



Ordering example

Product TRC200