

# Rectangular joint system

## Flange profile fasteners

### RJBC

Rectangular Joint Bolt Clamp



Clamp which is fastened over the flanges of the two rectangular ducts to fasten them to each other.

The clamp is easy to use where there is sufficient space to fasten the clamp.

### RJSP

Rectangular Joint Slide Profile



The slide profile does not demand space above the profile, but there has to be space at the side of the duct.

## Dimensions

Code	Dim	Length	Material	Thickness
RJBC			4404	3
RJBC			GALV	2,5
RJBC			GALV	3
RJSP	20	5000	4404	1
RJSP	40	5000	GALV	1,2
RJSP	2030	5000	GALV	1,2
M6S, M6SF	8	25	GALV	
M6S, M6SF	10	25	GALV	
M6M, M6MF	8		GALV	
M6M, M6MF	10		GALV	
RJSM	9	10000	PE	4
RJSM	9	10000	PE	6
RJSM	12	10000	PE	4

## Ordering example

	<b>RJBC</b>	<b>GALV</b>	<b>2,5</b>
Product			
Material			
Thickness			

## Corner fasteners

The M8 bolt and nut is to be used with all the RJCL 20 corners. The M10 bolt and nut is to be used with RJCL 30 and 40 corners.

### M6S, M6SF

Rectangular Joint Bolt



### M6M, M6MF

Rectangular Joint Nut



## Seal moulding

### RJSM

Rectangular Joint Seal Moulding



The 9 mm seal moulding is to be used with RJFP 20 profile

The 12 mm seal moulding is to be used with RJFP 30 and 40 profiles or as sealing in between two flanges FL, see catalogue page for FL for more information.