Roof adapter

TGR-OA




Description

Rectangular roof adapter, upper connection. TGR-OA is used when connecting roof hoods H, HV, HU, HN or HF to roof transition TGR.


For more information see <u>TGR</u>.

Dimensions



The C-measure of the upper connection shall fit the A-measure of the roof transition (TGR).

TGR



Ordering example

	TGR-OA	3	125	1
Product				Ī
Size				
Hood dimension				
Material			<u> </u>	
Zink plated steel		1		
Stainl. acid-res. steel 1.44	04	3		
Stainless steel 1.4301		4		

Roof adapter

TGR-OA

Connection scheme

Roof hood	H HV HU HN HF	VHL	LHR	HRR HVR				
	Hoods with circular connection		Hoods with rectangular connection					
Hood to adapter	Screw or bol	Guiding profile	The hood is					
Adapter	TGR-OA Ø80–315 Ø400–1250	TGR-VHL Ø100–315 Ø400–500	TGR-LHR	attached directly to the roof transition. – No adapter is needed.				
Adapter to roof transition	Screw							
Roof transition	TGR							
Roof transition to connector	Guiding profile							
Connector	TGR-NA	The roof transition is attached directly to the duct. – No connector is needed.						
Connector to duct	Screw, blind rivet or Lindab Click							
Duct	SR	LKR						

