



# Lindab **NC19**

Integra - Nozzle diffuser



# Integra - Nozzle diffuser

# NC19



## Description

NC19 is a circular diffuser with individually adjustable nozzles. The diffuser is suitable for the horizontal supply of cooled air, where great flexibility in the dispersal pattern is required. The diffuser can also be set to a vertical supply air pattern, enabling supply of heated air.

Installing a NC19 diffuser in a plenum box type MB can help to achieve a stable flow of air to the diffuser as well as realise the potential for individual adjustment.

Damper type B is an unique linear cone damper which allows to use the full operational area (0-100%) and allows to balance with a high pressure drop over the box with low sound generation. Furthermore the construction of the damper gives an accurate and reliable measurement.

Damper type C is with a rotating blade damper for supply air. Typically used in applications that don't require a high balancing pressure in the plenum box.

- Adjustable dispersal patterns
- No pressure change for different dispersal patterns
- Suitable for horizontal or vertical supply air patterns
- Plenum box with several damper options

## Maintenance


The face plate can be removed to enable cleaning of internal parts or to gain access to the duct or box. The visible parts of the diffuser can be wiped with a damp cloth.

## Order code

<b>Product</b>	<b>NC19</b>	-	<b>S</b>	-	<b>aaa</b>
<b>Type</b>	NC19				
<b>Functional use</b>	S = Supply air				
<b>Connection dim.</b>	Ød 125-315				

Example: NC19-S-200

## Dimensions



NC19 Ød	ØA	H	ØU*	m
mm	mm	mm	mm	kg
125	360	140	370	3.90
160	460	140	470	5.30
200	460	140	470	5.40
250	540	140	550	7.40
315	540	140	550	8.10

\* ØU = ceiling grid opening.

Ød 315, No mounting holes for MB !



## Materials and finish

Material: Galvanised steel  
 Standard finish: Powder-coated  
 Standard colours: RAL 9003 or RAL 9010, gloss 30  
 Nozzles: White ABS plastic


The diffuser is available in other colours. Please contact Lindab's sales department for further information.

# Integra - Nozzle diffuser


# NC19

## Accessories

### DCZ - Mounting brackets



### MBZ - Extension piece




#### Order code - accessories

Product aaa bbb  
 Type \_\_\_\_\_  
 Size \_\_\_\_\_

Example: DRZ-200

### LM - Module plate




#### Order code - module plate

Product LM a NC19 ccc  
 Type \_\_\_\_\_  
 Ceiling system \_\_\_\_\_  
 Diffuser \_\_\_\_\_  
 Size \_\_\_\_\_

Example: LM-1-NC19-200  
 Ceiling system - see introductory summary

## NC19 + MB plenum box




Ød <sub>1</sub> mm	Ød <sub>2</sub>	B	C	D	e	H*	L	W
mm								
100	125	62	245	78	40	256 - 296	310	260
100	160	62	245	78	40	256 - 296	310	260
125	125	75	291	78	40	281 - 321	376	310
125	160	75	291	78	40	281 - 321	376	310
125	200	75	291	78	40	221 - 261	376	310
160	160	92	352	78	40	315 - 355	459	380
160	200	92	352	78	40	315 - 355	459	380
160	250	92	352	78	40	315 - 355	459	380
200	200	112	425	78	40	356 - 396	565	460
200	250	112	425	78	40	356 - 396	565	460
200	315	112	425	78	40	356 - 396	565	460
250	250	137	514	118	60	406 - 446	698	540
250	315	137	514	118	60	406 - 446	698	540
315	315	170	675	118	60	471 - 511	858	540

\* Using accessory MBZ the H dimension will increase:

Ød<sub>2</sub> = 100 - 200 mm => H +40 mm

Ød<sub>2</sub> = 250 - 315 mm => H +60 mm

## Damper options



## Order code

Product MB a bbb ccc S  
 Type \_\_\_\_\_  
 MB \_\_\_\_\_  
 Damper \_\_\_\_\_  
 B = Linear cone damper  
 C = Blade damper supply  
 Duct connection Ød<sub>1</sub> \_\_\_\_\_  
 Ø100-315 \_\_\_\_\_  
 Diffuser dimension Ød<sub>2</sub> \_\_\_\_\_  
 Ø125-315 \_\_\_\_\_  
 Function (Only for B damper) \_\_\_\_\_  
 S = Supply air

Example 1: NC19-S-200+MBB-200-250-S

Example 2: NC19-200+MBC-125-200

# Integra - Nozzle diffuser

# NC19

## Technical data

Following NC19+plenum box data are valid for MBB-S. For MBC data, go to [www.lindQST.com](http://www.lindQST.com).

## Capacity

Air flow  $q_v$  [l/s] and [m<sup>3</sup>/h], total pressure  $\Delta p_t$  [Pa], throw  $l_{0,2}$  [m] and sound power level  $L_{WA}$  [dB(A)] can be seen in the diagrams.

## Frequency-related sound power level

The sound power level in the frequency band is defined as  $L_{WA} + K_{ok}$ .  $K_{ok}$  values are specified in charts beneath the diagrams on the following pages.



## Quick selection, supply air

NC19 + MBB-S		$\Delta p_t \geq 50$ Pa 30 dB(A)		$\Delta p_t \geq 50$ Pa 35 dB(A)	
duct	NC19	l/s	m <sup>3</sup> /h	l/s	m <sup>3</sup> /h
$\varnothing d_1$	$\varnothing d_2$				
100	125	25	90	33	119
100	160	39	140	47	169
125	125	35	126	41	148
125	160	48	173	59	212
125	200	54	194	64	230
160	160	52	187	63	227
160	200	59	212	72	259
160	250	76	274	96	346
200	200	66	238	80	288
200	250	92	331	112	403
200	315	97	349	120	432
250	250	100	360	119	428
250	315	109	392	131	472
315	315	121	436	143	515



## Throw $l_{0,2}$

Throw  $l_{0,2}$  [m] can be seen in the diagram for isothermal air, at a terminal velocity of 0.2 m/s.



## Sound attenuation

Sound attenuation of the diffusers  $\Delta L$  from duct to room, including and reflection, see table below.

NC19 + MBB-S		Centre frequency Hz							
duct	NC19	63	125	250	500	1K	2K	4K	8K
$\varnothing d_1$	$\varnothing d_2$								
100	125	20	16	6	15	20	20	19	23
100	160	16	16	4	13	18	19	17	21
125	125	17	15	10	19	20	20	19	22
125	160	15	14	7	18	18	18	18	21
125	200	13	12	5	15	15	16	17	19
160	160	16	15	11	22	20	20	20	20
160	200	16	15	8	21	19	19	19	21
160	250	16	14	5	17	14	16	18	19
200	200	15	10	8	16	20	18	20	18
200	250	13	9	5	13	17	15	19	17
200	315	13	9	4	11	16	15	17	17
250	250	14	8	8	16	18	18	18	19
250	315	14	8	6	14	17	16	17	18
315	315	8	10	9	14	17	17	18	24

## Balancing

Balancing data is contained in a separate brochure.




# Integra - Nozzle diffuser

# NC19


## Technical data

### Throws/Turning points

Throw  $l_{0,2}$  [m] is specified at a terminal velocity of 0.2 m/s.  
Turning point  $l_{0,0}$  [m] is specified for +5 K and +10 K respectively.



### NC19 without box – Supply air




# Integra - Nozzle diffuser

# NC19


## Technical data

### NC19 - 125 + MBB-S - Supply air




Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	11	1	-4	0	-5	-15	-23	-35


### NC19 - 160 + MBB-S - Supply air




Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	6	5	-3	-1	-4	-14	-21	-32



Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	10	3	2	0	-7	-15	-22	-27



Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	8	5	-1	-1	-6	-13	-17	-25




Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	10	4	1	0	-8	-12	-16	-21

# Integra - Nozzle diffuser

# NC19


## Technical data

### NC19 - 200 + MBB-S - Supply air




Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	11	2	-5	0	-4	-16	-23	-33


### NC19 - 250 + MBB-S - Supply air




Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	10	3	-4	-1	-4	-15	-23	-34




Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	9	4	-2	-1	-5	-14	-20	-28



Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	6	7	-2	-1	-4	-14	-20	-29



Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	6	5	0	0	-6	-12	-17	-25




Hz	63	125	250	500	1K	2K	4K	8K
$K_{ok}$	11	6	1	-2	-5	-12	-18	-26

# Integra - Nozzle diffuser


# NC19

## Technical data


### NC19 - 315 + MBB-S - Supply air



Hz	63	125	250	500	1K	2K	4K	8K
$K_{sk}$	9	1	-4	-1	-3	-17	-26	-40



Hz	63	125	250	500	1K	2K	4K	8K
$K_{sk}$	9	4	-2	-1	-4	-15	-23	-30



Hz	63	125	250	500	1K	2K	4K	8K
$K_{sk}$	8	7	0	-2	-5	-14	-20	-30





Most of us spend the majority of our time indoors. Indoor climate is crucial to how we feel, how productive we are and if we stay healthy.

We at Lindab have therefore made it our most important objective to contribute to an indoor climate that improves people's lives. We do this by developing energy-efficient ventilation solutions and durable building products. We also aim to contribute to a better climate for our planet by working in a way that is sustainable for both people and the environment.

[Lindab](#) | For a better climate