

DECLARATION OF PERFORMANCE N°5.9

DoP_WKS25n5rev9da29092025_E

1	Single identification code of the product-type	WKS25	
2	Intended use	Rectangular fire dampers leakage rated (500Pa / 300Pa) for use in heating, ventilation and air-conditioning (HVAC) systems at fire boundaries to maintain compartmentation and protect means of escape in case of fire.	
3	Manufacturer	MP3 srl - Via Giorgio La Pira, 9A/B- 35012 Camposampiero PD Italia	
4	Authorised representative	*	
5	Verification system of the constancy of performance	System 1	
6a	Harmonised standard	EN 15650 2010	
	Certificate of constancy of performance – CE	1812-CPR-1046	
	Notified body	Efectis France n° 1812	
	Certificate of constancy of performance – UKCA	2822-UKCA-CPR-0025	
	Notified body	Efectis UK / Ireland n° 2822	
6b	European assessment document	*	
	European technical assessment	*	
	Technical assessment body	*	
	Notified bodies	*	
7	Performances	The declared performances refer to the product used consistently with the intended use described in point 2 and correctly installed in accordance with the instructions in the technical manual and installation manual. In case of use different from the intended one and/or in the case of installation other than that described in the product’s technical manual and installation manual, no performance can be declared.	
Nominal activation conditions / sensitivity ISO 10294-4 ISO 21925-1		Sensing element load bearing capacity	Conform
		Sensing element response temperature	Conform
Response delay EN 1366-2		Closure time	<2 min Conform
Operational reliability EN 1366-2 EN 15650 – cycling test		Manual	50 cycles conforme
		Motorized	10000+100+100 cycles conform
		With magnet	100+100+100 cycles conform
Durability of response delay EN 15650 Sensing element response temperature and load bearing capacity		Conform	
Durability of operational reliability EN 15650 Open and closing cycle		Conform	
Tightness class of the casing class ATC 3 (old class C) up to +/-2000Pa EN 1751		Conform	
Salt spray exposure text severity class 2 EN 60068-2-52		Conform	

Fire resistance EN 1366-2 EN 13501-3	Integrity E	Insulation I	Smoke leakage S
	Mechanical stability (under E)	Mintenance of cross section (under E)	

(*) In accordance with EU Regulation 305/2011, points 4, 6b and 8 do not apply to this product.

DECLARATION OF PERFORMANCE N°5.9

DoP_WKS25n5rev9da29092025_E

	Position	Support features	Sealing	Note	Fire resistance class
Rigid wall	within the wall	Min.thickness 100 mm, density 550 kg/m ³	plasterboard or calcium silicate	A B E F	EI 120 (ve i↔o) S (500Pa)
Light wall	within the wall	F-type plasterboard wall min. thickness 100mm, metal studs, optional rock wool insulation, optional sheet metal safety reinforcement	plasterboard or calcium silicate	A B E F	EI 120 (ve i↔o) S (500Pa)
		A-type plasterboard wall min. thickness 100mm, metal studs, optional rock wool insulation	plasterboard or calcium silicate	A B E F	EI 60 (ve i↔o) S (500Pa)
		in gypsum blocks min. thickness 100mm	plasterboard or calcium silicate	A B E F	EI 120 (ve i↔o) S (500Pa)
		in gypsum blocks min. thickness 70mm	plasterboard or calcium silicate	A C D F	EI 90 (ve i↔o) S (500Pa)
		shaft plasterboard wall min. thickness 90mm	plasterboard	A C D F	EI 90 (ve i↔o) S (300Pa)

NOTE	A installation without duct connection permitted	B minimum distance between two fire dampers 0mm
	C minimum distance between two fire dampers 200mm	D 75mm between fire damper and ceiling or side wall
	E 0mm between fire damper and ceiling or side wall	F blade axis direction horizontal or vertical

8	Appropriate technical documentation and/or specific technical documentation	*
9	Declaration	The performances of the product referred to in point 1 are in conformity with the declared performances declared under point 7. This declaration of performances is established under the sole responsibility of the manufacturer identified in point 3.

Available servomotors	BELIMO	BFL 24 T – BFL 24 TST – BFL230 T
	GRUNER	340TA-024-05-S2- 340TA-230-05-S2- 340TA-024-05-ST01
	SIEMENS	GRA 126 1E T12- GNA 126 1E T12 GRA 326 1E T12- GNA 326 1E T12

Camposampiero, 29/09/2025


Giuseppe Lanzilao
General Manager MP3

(*) In accordance with EU Regulation 305/2011, points 4, 6b and 8 do not apply to this product.