

DOP Declaration of Performance LHP130.docx

Declaration of Performance EN 1090 - Load bearing profiles

Declaration of Performance number

B-2461

Unique identification code

LHP 130

Intended use of the product

Structural steel sheet for use in roofs

Manufacturer

Lindab Profil AB, 269 82 Båstad

System of assessment and verification

LIOII

of constancy of performance

2+ EN 1090-1

Harmonised European standard

LIV 1030 I

Notified body

KIWA certificate number 0416-CPD-6624-01

Information on regulated characteristics

Geometrical tolerances

EN 1090-4

Weldability

NPD

Fracture toughness

NPD

Load bearing capacity

According to EN 1993-1-3 and design calculations with

Lindab software Industrial

Manufacturing:

According to EN 1090-4 and component specification,

internal doc 1005 (se Annex A1-A2 EN1090-2)

Execution class EXC1 - EXC4

Deformation at serviceability

limit state

NPD

Fatigue strength Resistance to fire NPD NPD

Reaction to fire

Polyester coating SP 15:

Class A2 - s1, d0

Galvanized:

Class A1

Release of cadmium

NPD

Emission of radioactivity

NPD Coatings performances are:

Durability

Hot-dip coating with Z275 and without any organic coating

Hot-dip coating with ZM100 and with polyester coating - PE15

Material

S420GD+ZM100 according to EN 10346

S420GD+ZM275 according to EN 10346

Normal thickness tolerance according to EN 10143

Luleå 2023-06-26

Vidar Hammersland

Product Manager, Building Projects



Dok. Nr 2461 Utfärdare LPHO Utf. Datum 18-05-23 Rev. 4.0 Rev. Datum 23-06-26 Sida 1(1)